

MODEL No.
850

Cuts cables up to 85 mm



SPECIFICATIONS

Maximum handle load : 196 N
 Two stage pumping
 Relief valve is not equipped
 Reservoir capacity : 120 cc
 Maximum opening : 88 mm
 Pumping cycles when no load : 20 times

Output force : 39 kN

SIZE

710 (L) mm

WEIGHT

8.2 kg

ACCESSORIES

Carrying bag

850



850 (Head opened)

FEATURES

Light weight portable hydraulic cutter features :

- * Two stage pumping for rapid blade advance
- * Guillotine type cutting for less jamming than shear type cutting
- * No set-up time required
- * Blades are easily replaceable
- * 180 degree swivel and lock pin type head allows easy cutting position

REMARKS

Cutting of piano wire is prohibited.

Cutting capacity

| | |
|------------------|---------|
| Cu strands | : 28 mm |
| Al strands | : 38 mm |
| CCP cable | : 85 mm |
| Wire rope 6 x 7 | : N/A |
| Wire rope 6 x 12 | : N/A |
| Wire rope 6 x 19 | : N/A |
| Soft steel bar | : N/A |
| Reinforcing rod | : N/A |
| ACSR | : N/A |
| Guy wire 1 x 7 | : N/A |
| Guy wire 1 x 19 | : N/A |