

MODEL No.

SH-10(A)P SH-10(B)P

Up to 115.5 mm diameter hole perforation on 3.2 mm thickness mild steel



SH-10 (B) P



SH-10(A)P shown with carrying case

SPECIFICATIONS

Punching capacity
Stainless Steel :
1.6 mm plate thickness
Mild steel :
3.2 mm plate thickness
Hole diameter :

up to 115.5 mm (4 inches)
Ram Stroke : 25 mm
Oil volume required : 35 cc
Output force : 81 kN at 68.5 Mpa pressure

SIZE

63 (Dia) x 125 (H) mm

WEIGHT

1.9 kg

ACCESSORIES

Milli size punch sets are available on request.

M15, 16, 25, 30, 35, 40, 45, 50, 55, 57, 67, 70, 80, 82, 87, 95, 100, 108, 110

FEATURES

Selection Chart :

SH-10 (A) P SH-10 (B) P

- 1 HP-180N Hand Pump
- 2 Setting threads (3/8" & 3/4")
- 3 Collar (Large, Medium, Small)
- 4 Steel carrying case

A19 (3/4")	B16 (1/2")
A25 (1")	B22 (3/4")
A31 (1 1/4")	B28 (1")
A39 (1 1/2")	B36 (1 1/4")
A51 (2")	B42 (1 1/2")
	B54(2")

REMARKS

Punching size

Punch	Hole size
A15*	17.6 mm
A19 (3 / 4)	19.8 mm
A25 (1)	26.1 mm
A31 (1 1/ 4)	32.5 mm
A39 (1 1/ 2)	38.7 mm
A51 (2)	51.6 mm
A63 (2 1/ 2)*	64.4 mm
A75 (3)*	77.2 mm
B16 (1/ 2)	21.8 mm
B22 (3 / 4)	27.6 mm
B28 (1)	34.1 mm
B36 (1 1/ 4)	42.7 mm
B42 (1 1/ 2)	48.7 mm
B54 (2)	60.5 mm
B70 (2 1/ 2)*	76.1 mm
B82 (3)*	88.9 mm
B92 (3 1/ 2)*	102.8 mm
B104 (4)*	115.5 mm

(*) marks show optional punch set available