

RELEASABLE CABLE TIES UNCOATED / COATED



Technical information:

Releasable Cable Tie : Releasable Type Cable Tie can be used for multiple installations over long period of time

Material : A) 316 grade non-magnetic stainless steel
B) 304 grade non-magnetic stainless steel

Temperature Range : -60°C to +300°C

Surface Finish : Metallic

Flamability Rating : UL94 fireproof, Halogen free and UV-resistant

Releasable Cable Ties - Uncoated - 6.35mm width

Part No. for Stainless Steel Grade		Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
SS304	SS316	In	mm	In	mm	In	mm	In	mm	N	lbs	
RU54-150	RU56-150	1/4	6.35	6	150	0.02	0.50	1.3	34	1334	300	100/bag
RU54-230	RU56-230	1/4	6.35	9	230	0.02	0.50	2.3	59	1334	300	100/bag
RU54-330	RU56-330	1/4	6.35	13	330	0.02	0.50	3.6	91	1334	300	100/bag
RU54-450	RU56-450	1/4	6.35	18	450	0.02	0.50	5.0	129	1334	300	100/bag
RU54-600	RU56-600	1/4	6.35	24	600	0.02	0.50	7.0	177	1334	300	100/bag
RU54-750	RU56-750	1/4	6.35	30	750	0.02	0.50	8.6	225	1334	300	100/bag
RU54-900	RU56-900	1/4	6.35	35	900	0.02	0.50	10.8	273	1334	300	100/bag

Releasable Type - Uncoated - 9.53mm width

RU104-150	RU106-150	3/8	9.53	6	150	0.02	0.50	1.3	34	1334	300	100/bag
RU104-230	RU106-230	3/8	9.53	9	230	0.02	0.50	2.3	59	1334	300	100/bag
RU104-330	RU106-330	3/8	9.53	13	330	0.02	0.50	3.6	91	1334	300	100/bag
RU104-450	RU106-450	3/8	9.53	18	450	0.02	0.50	5.0	129	1334	300	100/bag
RU104-600	RU106-600	3/8	9.53	24	600	0.02	0.50	7.0	177	1334	300	100/bag
RU104-750	RU106-750	3/8	9.53	30	750	0.02	0.50	8.6	225	1334	300	100/bag
RU104-900	RU106-900	3/8	9.53	35	900	0.02	0.50	10.8	273	1334	300	100/bag

Releasable Cable Ties - Coated - 6.35mm width

RC54-150	RC56-150	1/4	6.35	6	150	0.02	0.50	1.3	34	1334	300	100/bag
RC54-230	RC56-230	1/4	6.35	9	230	0.02	0.50	2.3	59	1334	300	100/bag
RC54-330	RC56-330	1/4	6.35	13	330	0.02	0.50	3.6	91	1334	300	100/bag
RC54-450	RC56-450	1/4	6.35	18	450	0.02	0.50	5.0	129	1334	300	100/bag
RC54-600	RC56-600	1/4	6.35	24	600	0.02	0.50	7.0	177	1334	300	100/bag
RC54-750	RC56-750	1/4	6.35	30	750	0.02	0.50	8.6	225	1334	300	100/bag
RC54-900	RC56-900	1/4	6.35	35	900	0.02	0.50	10.8	273	1334	300	100/bag

Releasable Type - Coated - 9.53mm width

RC104-150	RC106-150	3/8	9.53	6	150	0.02	0.50	1.3	34	1334	300	100/bag
RC104-230	RC106-230	3/8	9.53	9	230	0.02	0.50	2.3	59	1334	300	100/bag
RC104-330	RC106-330	3/8	9.53	13	330	0.02	0.50	3.6	91	1334	300	100/bag
RC104-450	RC106-450	3/8	9.53	18	450	0.02	0.50	5.0	129	1334	300	100/bag
RC104-600	RC106-600	3/8	9.53	24	600	0.02	0.50	7.0	177	1334	300	100/bag
RC104-750	RC106-750	3/8	9.53	30	750	0.02	0.50	8.6	225	1334	300	100/bag
RC104-900	RC106-900	3/8	9.53	35	900	0.02	0.50	10.8	273	1334	300	100/bag