

BALL LOCK CABLE TIES UNCOATED



Technical information:

Material	: A) 316 grade non-magnetic stainless steel
	: B) 304 grade non-magnetic stainless steel
Temperature Range	: -60°C to +300°C
Surface Finish	: Metallic
Flamability Rating	: UL94 fireproof, Halogen free and UV-resistant
Multicolour	: Available

Ball Lock Uncoated - 4.6mm width

Part No. for Stainless Steel Grade		Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
SS304	SS316	In	mm	In	mm	In	mm	In	mm	N	lbs	
BU44-100	BU46-100	0.18	4.6	4	100	0.01	0.25	0.7	18	445	100	100/bag
BU44-150	BU46-150	0.18	4.6	6	150	0.01	0.25	1.3	34	445	100	100/bag
BU44-200	BU46-200	0.18	4.6	8	200	0.01	0.25	2.0	50	445	100	100/bag
BU44-260	BU46-260	0.18	4.6	10	260	0.01	0.25	2.7	69	445	100	100/bag
BU44-360	BU46-360	0.18	4.6	14	360	0.01	0.25	3.9	100	445	100	100/bag
BU44-520	BU46-520	0.18	4.6	20	520	0.01	0.25	5.9	151	445	100	100/bag
BU44-620	BU46-620	0.18	4.6	24	620	0.01	0.25	7.2	183	445	100	100/bag
BU44-840	BU46-840	0.18	4.6	33	840	0.01	0.25	10.0	253	445	100	100/bag
BU44-1000	BU46-1000	0.18	4.6	39	1000	0.01	0.25	12.0	304	445	100	100/bag

Ball Lock Uncoated - 7.9mm width

BU74-100	BU76-100	0.31	7.9	4	100	0.01	0.25	0.7	18	1112	250	100/bag
BU74-150	BU76-150	0.31	7.9	6	150	0.01	0.25	1.3	34	1112	250	100/bag
BU74-200	BU76-200	0.31	7.9	8	200	0.01	0.25	2.0	50	1112	250	100/bag
BU74-260	BU76-260	0.31	7.9	10	260	0.01	0.25	2.7	69	1112	250	100/bag
BU74-360	BU76-360	0.31	7.9	14	360	0.01	0.25	3.9	100	1112	250	100/bag
BU74-520	BU76-520	0.31	7.9	20	520	0.01	0.25	5.9	151	1112	250	100/bag
BU74-620	BU76-620	0.31	7.9	24	620	0.01	0.25	7.2	183	1112	250	100/bag
BU74-840	BU76-840	0.31	7.9	33	840	0.01	0.25	10.0	253	1112	250	100/bag
BU74-1000	BU76-1000	0.31	7.9	39	1000	0.01	0.25	12.0	304	1112	250	100/bag

Ball Lock Uncoated - Heavy Duty - 12.7mm width

BU124-100	BU126-100	0.50	12.7	4	100	0.02	0.40	0.7	18	3115	700	100/bag
BU124-150	BU126-150	0.50	12.7	6	150	0.02	0.40	1.3	34	3115	700	100/bag
BU124-200	BU126-200	0.50	12.7	8	200	0.02	0.40	2.0	50	3115	700	100/bag
BU124-260	BU126-260	0.50	12.7	10	260	0.02	0.40	2.7	69	3115	700	100/bag
BU124-360	BU126-360	0.50	12.7	14	360	0.02	0.40	3.9	100	3115	700	100/bag
BU124-520	BU126-520	0.50	12.7	20	520	0.02	0.40	5.9	151	3115	700	100/bag
BU124-620	BU126-620	0.50	12.7	24	620	0.02	0.40	7.2	183	3115	700	100/bag
BU124-840	BU126-840	0.50	12.7	33	840	0.02	0.40	10.0	253	3115	700	100/bag
BU124-1000	BU126-1000	0.50	12.7	39	1000	0.02	0.40	12.0	304	3115	700	100/bag

Ball Lock Uncoated - Heavy Duty - 16.0mm width

BU164-150	BU166-150	0.63	16.0	6	150	0.02	0.40	1.3	34	800	3560	100/bag
BU164-200	BU166-200	0.63	16.0	8	200	0.02	0.40	2.0	50	800	3560	100/bag
BU164-260	BU166-260	0.63	16.0	10	260	0.02	0.40	2.7	69	800	3560	100/bag
BU164-360	BU166-360	0.63	16.0	14	360	0.02	0.40	3.9	100	800	3560	100/bag
BU164-520	BU166-520	0.63	16.0	20	520	0.02	0.40	5.9	151	800	3560	100/bag
BU164-620	BU166-620	0.63	16.0	24	620	0.02	0.40	7.2	183	800	3560	100/bag
BU164-840	BU166-840	0.63	16.0	33	840	0.02	0.40	10.0	253	800	3560	100/bag
BU164-1000	BU166-1000	0.63	16.0	39	1000	0.02	0.40	12.0	304	800	3560	100/bag