

BALL LOCK CABLE TIES COATED



Technical information:

Material	: A) 316 grade non-magnetic stainless steel B) 304 grade non-magnetic stainless steel
Temperature Range	: -60°C to +150°C
Surface Finish	: Pure Polyester and Epoxy Coatings
Flamability Rating	: UL94 fireproof, Halogen free and UV-resistant
Multicolour	: Available

Ball Lock Coated - 4.6mm width

Part No. for Stainless Steel Grade		Width		Length		Thickness		Max Diameter Single Loop		Minimum Loop Tensile Strength		Package Quantity
SS304	SS316	In	mm	In	mm	In	mm	In	mm	N	lbs	
BC44-100	BC46-100	0.18	4.6	4	100	0.01	0.25	0.7	18	445	100	100/bag
BC44-150	BC46-150	0.18	4.6	6	150	0.01	0.25	1.3	34	445	100	100/bag
BC44-200	BC46-200	0.18	4.6	8	200	0.01	0.25	2.0	50	445	100	100/bag
BC44-260	BC46-260	0.18	4.6	10	260	0.01	0.25	2.7	69	445	100	100/bag
BC44-360	BC46-360	0.18	4.6	14	360	0.01	0.25	3.9	100	445	100	100/bag
BC44-520	BC46-520	0.18	4.6	20	520	0.01	0.25	5.9	151	445	100	100/bag
BC44-620	BC46-620	0.18	4.6	24	620	0.01	0.25	7.2	183	445	100	100/bag
BC44-840	BC46-840	0.18	4.6	33	840	0.01	0.25	10.0	253	445	100	100/bag
BC44-1000	BC46-1000	0.18	4.6	39	1000	0.01	0.25	12.0	304	445	100	100/bag

Ball Lock Coated - 7.9mm width

BC74-100	BC76-100	0.31	7.9	4	100	0.01	0.25	0.7	18	1112	250	100/bag
BC74-150	BC76-150	0.31	7.9	6	150	0.01	0.25	1.3	34	1112	250	100/bag
BC74-200	BC76-200	0.31	7.9	8	200	0.01	0.25	2.0	50	1112	250	100/bag
BC74-260	BC76-260	0.31	7.9	10	260	0.01	0.25	2.7	69	1112	250	100/bag
BC74-360	BC76-360	0.31	7.9	14	360	0.01	0.25	3.9	100	1112	250	100/bag
BC74-520	BC76-520	0.31	7.9	20	520	0.01	0.25	5.9	151	1112	250	100/bag
BC74-620	BC76-620	0.31	7.9	24	620	0.01	0.25	7.2	183	1112	250	100/bag
BC74-840	BC76-840	0.31	7.9	33	840	0.01	0.25	10.0	253	1112	250	100/bag
BC74-1000	BC76-1000	0.31	7.9	39	1000	0.01	0.25	12.0	304	1112	250	100/bag

Ball Lock Coated - Heavy Duty - 12.7mm width

BC124-100	BC126-100	0.50	12.7	4	100	0.02	0.4	0.7	18	3115	700	100/bag
BC124-150	BC126-150	0.50	12.7	6	150	0.02	0.4	1.3	34	3115	700	100/bag
BC124-200	BC126-200	0.50	12.7	8	200	0.02	0.4	2.0	50	3115	700	100/bag
BC124-260	BC126-260	0.50	12.7	10	260	0.02	0.4	2.7	69	3115	700	100/bag
BC124-360	BC126-360	0.50	12.7	14	360	0.02	0.4	3.9	100	3115	700	100/bag
BC124-520	BC126-520	0.50	12.7	20	520	0.02	0.4	5.9	151	3115	700	100/bag
BC124-620	BC126-620	0.50	12.7	24	620	0.02	0.4	7.2	183	3115	700	100/bag
BC124-840	BC126-840	0.50	12.7	33	840	0.02	0.4	10.0	253	3115	700	100/bag
BC124-1000	BC126-1000	0.50	12.7	39	1000	0.02	0.4	12.0	304	3115	700	100/bag

Ball Lock Coated - Heavy Duty - 16.0mm width

BC164-150	BC166-150	0.63	16.0	6	150	0.02	0.40	1.3	34	3560	800	100/bag
BC164-200	BC166-200	0.63	16.0	8	200	0.02	0.40	2.0	50	3560	800	100/bag
BC164-260	BC166-260	0.63	16.0	10	260	0.02	0.40	2.7	69	3560	800	100/bag
BC164-360	BC166-360	0.63	16.0	14	360	0.02	0.40	3.9	100	3560	800	100/bag
BC164-520	BC166-520	0.63	16.0	20	520	0.02	0.40	5.9	151	3560	800	100/bag
BC164-620	BC166-620	0.63	16.0	24	620	0.02	0.40	7.2	183	3560	800	100/bag
BC164-840	BC166-840	0.63	16.0	33	840	0.02	0.40	10.0	253	3560	800	100/bag
BC164-1000	BC166-1000	0.63	16.0	39	1000	0.02	0.40	12.0	304	3560	800	100/bag