

# U-GLAND

# BW Type

## STANDARD

B.S.6121 PART - 1 : 1989

## APPLICATION

Dry Indoor, for use with all types of (SWA & AWA) Cables

## FUNCTION

Provides mechanical cable retention and electrical continuity via Armour wire termination.



Material : Brass

All Dimensions Are Milimeter

GLAND SIZE	ENTRY THREAD		CABLE ACCEPTANCE DETAIL			ACROSS FLAT G	ACROSS CORNER H
	DIA. D	LENGTH MINIMUM E	DIAMETER MIN. MAX. A	DIAMETER MIN. MAX. B	ARMOUR DIAMETER		
20 S	20	10	11.8	17.2	0.9 / 1.25	23.5	26.5
20 L	20	10	14.0	20.8	0.9 / 1.25	27.2	30.5
25 S	25	15	18.5	24	1.25 / 1.60	31.5	35.0
25 L	25	15	20.3	27.2	1.25 / 1.60	35.0	39.0
32 S	32	10	24.0	31.0	1.60 / 2.00	41.0	45.0
32 L	32	10	26.2	34.0	1.60 / 2.00	43.0	47.5
40 S	40	15	30.0	38.5	1.60 / 2.00	48.0	53.5
40 L	40	15	32.2	40.5	1.60 / 2.00	51.5	57.0
50 S	50	15	38.2	46.8	2.00 / 2.50	58.5	65.0
50 L	50	15	44.0	53.2	2.00 / 2.50	64.0	71.0
63 S	63	15	50.0	59.0	2.50	72.0	80.0
63 L	63	15	56.0	66.0	2.50	79.0	88.0
75 S	75	17	62.0	72.0	2.50	86.5	97.0
75 L	75	17	68.0	78.0	2.50	94.0	105.0
90 L	90	20	79.0	90.0	2.50 / 3.15	105.0	117.0