

# ARRO

## LSZH PE COATED GALVANIZED FLEXIBLE CORRUGATED CONDUIT

- Galvanized steel strip square locked.
- Water resistant.
- Very flexible suitable for a wide range of applications.
- Available in PE coated and Low smoke, zero halogen in Black, white colour upon request.
- Tested accordingly to IEC 61034-2:2013 and IEC 60754-1 standard.
- Use with suitable water tight connector will provide IP66 rating.

Part Number	Inner Diameter mm	Outer Diameter mm	Connector Size mm	Connector Size inc	Length of Each Roll Mtr	Min Bending Radius mm
LSZH 16	16.3	20.3	M 20	1/2"	30	65
LSZH 20	21.3	25.3	M 25	3/4"	30	75
LSZH 25	27.1	32.0	M 32	1"	30	100
LSZH 32	35.8	40.8	M 40	1-1/4"	30	125
LSZH 38	40.7	47.3	M 50	1-1/2"	20	150
LSZH 51	52	60.0	M 63	2"	20	175

The above data might be changed without prior notice. Special size are available on request.

### APPLICATION

Seals out abrasives, alcohol, fumes, gases, dirt, oils, water and spray suitable for the following potentials:

- Underground railway, Tunnels
- Hospitals, Public places
- Machine tools
- Air conditioning / Ventilation
- Computer / Underfloor applications
- Airports, public building and halogen free areas (LSZH)

