


OSLN



[OSLN]



[OSLN-T]



Application : Lock Nut

- Secure a cable gland in position of the equipment
- Material : Nickel plated brass(Standard), Brass(only), Stainless steel(316L)

Order Example

Model	Thread size	Material
OSLN	M16	Nickel plated brass

● Metric & NPT/PF Type

(* in mm)

Type	Metric Thread			Type	NPT & PF Thread		
Part No.	H	P	L	Part No.	H	P	L
OSLN M16	22	25	4	OSLN 1/2"	27	31	4
OSLN M20	27	31	4	OSLN 3/4"	32	36	4
OSLN M25	32	36.5	4	OSLN 1"	39	45	5
OSLN M32	39	44.5	5	OSLN 1-1/4"	48	55.5	5
OSLN M40	48	55	5	OSLN 1-1/2"	60	67	6
OSLN M50	60	69	5	OSLN 2"	73	87	6
OSLN M63	73	84	6	OSLN 2-1/2"	85	98	6
OSLN M75	85	98	6	OSLN 3"	102	119	10
OSLN M90	102	117	10	OSLN 3-1/2"	112	126	12
OSLN M100	112	128	12	OSLN 4"	125	144	12
OSLN M115	125	144	12				

● PG Type

(* in mm)

Type	PG Thread			Type	Metric Thread		
Part No.	H	P	L	Part No.	H	P	L
OSLN PG7	15	31	3	OSLN PG M12	14	15	3
OSLN PG9	18	36	3	OSLN PG M16	18	20	3
OSLN PG11	21	45	3	OSLN PG M20	22	25	3
OSLN PG13.5	23	55.5	3	OSLN PG M25	27	30	4
OSLN PG16	26	67	3	OSLN PG M32	36	40	4
OSLN PG21	32	84	4	OSLN PG M40	45	50	5
OSLN PG29	41	98	4	OSLN PG M50	54	59	5
OSLN PG36	51	119	5	OSLN PG M63	67	73	6
OSLN PG42	60	126	5				
OSLN PG48	66	144	6				

Note.
For OSPG-R metric thread type.