




TAP-OFF CONNECTOR (C-CONNECTOR)

The range of C-CONNECTORS are manufactured in 'C' shaped copper section for connection of main and tap copper conductors.




- Approved by NTT corporation
- Reliability is ensured by passing tests specified by JIS C 2810
- Suitable for connecting copper conductors in both indoor and outdoor such as wiring in building or wiring in tunnel
- Tin plated to avoid rusting




(T-11 ~ T-122) (T-154 ~ T-700)
except T-20, T-26, T-44

Connector Size	Dimensions (mm)						Installation		Total Sectional area of applicable wire
	H1	H2	W	L	T	C	# of crimps	S	
T-11	9.5	6.3	6.2	12	1.6	4.0	2	7	7.5~11mm ²
T-16	11.8	7.8	7.8	13	2.0	5.0	2	8	11.5~16
T-20	12.8	8.4	9.7	13	2.9	5.1	1		14~20
T-26	14.7	10.2	10.9	16	3.2	6.5	1		21~26
T-44	19.0	13.4	14.4	20	4.0	8.5	1		27~44
T-60	21.0	15.4	15.1	22	4.0	9.7	2	11	45~60
T-76	24.4	17.3	17.6	22	5.0	10.8	2	11	61~76
T-98	27.8	20.8	18.8	25	5.0	13.8	2	11	77~98
T-122	29.8	22.1	21.2	26	5.5	13.5	2	12	99~122
T-154	34.0	25.7	24.4	28	6.0	17.0	3	8.5	123~154
T-190	37.0	28.5	25.4	35	6.0	17.4	3	10.5	155~190
T-240	40.0	30.2	28.5	40	7.0	19.0	3	13	191~240
T-288	44.5	34.7	31.1	45	7.0	22.3	3	14.5	241~288
T-365	47.5	37.7	34.0	50	7.0	24.8	3	16	289~365
T-450	57.0	42.5	41.0	60	10.0	28.0	3	18.5	366~450
T-560	62.0	46.0	45.0	65	11.0	31.0	3	20	451~560
T-700	68.0	51.0	49.5	70	12.0	34.0	3	21	561~700



Branch connection



Parallel connection

