

MV cables Tools

CWB/18-60



Section

MV Semi-conductor

Application

Field
Laboratory



PRODUCT BENEFITS

No silicon needed
Fine tuning of the blade with a 'click' for each 1/10 mm
Very smooth finish over the insulation
Adjustable length of semiconductor cutback : 25-30-40 mm / 0,984-1,181-1.575 in

TOOL CAPACITY

Diameter 18 - 60 mm
0,709 - 2,362 inch

Thickness capacity 1,1 mm / 0,043 in

Angle of the chamfer on the semiconductor 8°

Remaining length of the semiconductor 25-30-40 mm / 0,984-1,181-1,575 in

TOOL DIMENSIONS

Length 235 mm

Width 125 mm

Height 90 mm

Weight without box 0,85 Kg

Packaging Box

Tool to remove bonded semiconductor with chamfer on the semiconductor cutback

TO DO WHAT

The CWB/18-60 enables the user to easily remove the bonded semi-conductor with a chamfer on the transition, leaving a very smooth finish over the insulation
The CWB 18-60 works without silicone



Options

SGM - Large size pouch

Spare part

LCWB-SP2 - Spare blade for bonded semiconductor with chamfer 8°

Associated tool

LCWB-FEP - Spare blade for bonded semiconductor with chamfer 13°

GRI-RTE - Scraper for residues of bonded semiconductor screen with protective case

PG3HTA/2530 - Pliers for MV cables outer sheath

BRMRD1E - Tool to remove insulation

MV cables Tools

CWB/18-60



| Part Number | Diameter | Tool capacity | | | Dimensions | | | Packaging |
|----------------------|--------------------------------|--------------------|---|---------------------------------------|--------------------|--------------------|-------------------|-----------|
| | | Thickness capacity | Angle of the chamfer on the semiconductor | Remaining length of the semiconductor | Length | Width | Height | |
| CWB/18-60 | 18 - 60 mm 0,709 - 2,362 in | 1,1 mm / 0,043 in | 8° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | box |
| CWB/18-60-FEP | 18 - 60 mm 0,709 - 2,362 in | 1,8 mm / 0,071 in | 13° | 25-30-40 mm / 0,984-1,181-1,575 in | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | box |
| CWB/18-60-MVS | 18 - 60 mm 0,709 - 2,362 in | 1,8 mm / 0,071 in | 13 ° | With MVS stop | 235 mm 9,252 in | 125 mm 4,921 in | 90 mm 3,543 in | box |