



■ GLB

➔ Insulating latex gloves



➔ STANDARD(S)

EN 60903: 2003 / IEC 60903: 2002 PPE Category III = Irreversible risks

➔ USE

Insulation of hands by class and according to the nominal supply voltage.
Must be used with a pair of leather overgloves for a mechanical protection.

➔ SPECIFICATIONS

Beige natural latex insulating gloves for electricians, cut edges.

➔ ADVANTAGES

Its ergonomic shape and lightly powdered interior make the glove easy to slip on and off.
Its natural latex base offers high dielectric characteristics.

Reference	Description	Class	Max operating voltage	Length	Catégories	Size
GLB00-36	Insulating latex gloves 36 cm class 00	00	500V AC		AZC	07 to 12
GLB0-36	Insulating latex gloves class 0	0	1 000V AC		AZC	07 to 12
GLB1-36	Insulating latex gloves class 1	1	7 500V AC		RC	07 to 12
GLB2-36	Insulating latex gloves class 2	2	17 000V AC		RC	08 to 12
GLB3-36	Insulating latex gloves class 3	3	26 500V AC		RC	08 to 12
GLB4-41	Insulating latex gloves class 4	4	36 000V AC		RC	08 to 12

Document not contractually binding, errors and omissions excepted.



▶ TABLE LEGEND

Complete the reference with the desired size, example : GLB1-36-10 for a pair of gloves class 1 size 10.
Other colours available on request (red or black). Other lengths available on request (28 and 41 cm according to the class).

Document not contractually binding, errors and omissions excepted.



815B, chemin de Razas - 26780 Malataverne - France
+33 (0)4 75 90 58 00 - www.sf-electric.com

