

# Canon CABLE ID PRINTER MK3000

Delighting You Always

## Specifications

<b>Model</b>	<b>MK3000</b>	
<b>Printng Method</b>	Thermal Transfer	
<b>Printing Resolution (max.)</b>	300 dpi	
<b>Printing Speed (Tube)</b>	<b>High Speed</b>	25 pcs / min
	<b>Meddle Speed</b>	-
	<b>Low Speed</b>	18.5 mm/s
<b>Output Rate <sup>1</sup> (approx.)</b>	<b>High Speed</b>	35 pcs / min
	<b>Meddle Speed</b>	-
	<b>Low Speed</b>	30 pcs / min
<b>Ink Ribbon</b>	<b>Type</b>	Ribbon Cassette
	<b>For Tube and Label</b>	Black: 150 m / Black: 40 m / White: 85 m
	<b>For Plate</b>	-
<b>Cut Length</b>	<b>Tube</b>	8 - 150 mm
	<b>Label Tape / Plate</b>	4 - 150 mm
<b>Character Size</b>	1.3 mm (only full-width available) 2 mm, 2.6 mm, 3 mm, 4 mm, 6 mm (half-width, full-width available)	
<b>Number of Lines</b>	Up to 2 lines	
<b>Input Mode</b>	Alphanumeric, Symbol Input	
<b>Display</b>	<b>Type</b>	LCD (160 x 64 dots) with backlight
	<b>Capacity</b>	10 characters/line x 2 lines (full-width)
<b>Built-in Memory</b>	<b>Print Data Storage</b>	5,000 characters
	<b>File Storage</b>	250,000 characters, up to 10 folders
<b>Media Cutting Method</b>	Automatic Full-Cut, Automatic Half-Cut	
<b>Power Supply</b>	<b>AC Adaptor</b>	100 - 240 V, 50/60 Hz, 0.74A
	<b>Rechargeaber Batteries <sup>2</sup></b>	Panasonic enloop AA size (model: BK-3MCCE) x 6 pieces
<b>Power Consumption</b>	<b>Maximum</b>	24 W
<b>Interface</b>	USB 2.0 Full-Speed (USB 1.1 compatible)	
<b>Operating Environment</b>	<b>Temperature</b>	15 - 32.5°C (5 - 18°C with optional tube warmer installed)
	<b>Humidity</b>	10 - 85% RH (with no condensation)
<b>Storage Environment</b>	<b>Temperature</b>	5 - 35°C
	<b>Humidity</b>	10 - 90% RH (with no condensation)
<b>Dimensions (cm) ( W x D x H ) (approx.)</b>	27.2 x 31.8 x 9.7 cm	
<b>Weight (Kg) (approx.)</b>	2.7 Kg ( excluding accessories)	
<b>Print Media</b>	<b>PVC / Clear Tape</b>	Inner Diameter: Ø1.5 - 10 mm, Ø1.5 - 6.5 mm (when using tube warmer) Thickness: 0.4 - 0.6 mm
	<b>Heat Shrink Tube</b>	Inner Diameter: Ø1.5 - 10 mm Thickness: 0.2 - 0.4 mm
	<b>Label Tape</b>	Tape cassette (White, Yellow, Silver) Width: 6 mm, 9 mm, 12 mm Length: 30 m (White, Yellow), 27 m (Silver)
	<b>Flat Tube <sup>3</sup></b>	Diameter: Ø1.5 - 6.5mm Width: 11.2 mm or Less Thickness: 0.4 - 0.6 mm
	<b>Plate <sup>3</sup></b>	-

Specifications are subject to change without notice.

<sup>1</sup> Printing on 20 mm long tubes each, five 3 mm full-width characters, continuous print mode, half-cut with normal cutting strength.

<sup>2</sup> Batteries are not included with the printer. Only Panasonic enloop 1.2V AA rechargeable batteries (model: BK-3MCCE) should be used to avoid printer safety and warranty issues. "Panasonic" and "enloop" are registered trademarks of Panasonic Group.

<sup>3</sup> Plate & Flat Tube attachment (optional) is required for printing on plates or flat tubes.

**Canon** Authorized Distributor  
Delighting You Always

**Liko TRADE CENTRE PTE LTD**

Blk 31, Defu Lane 10, #04-60, Singapore 539212

Tel : (65) 6284 1819 Fax : (65) 6284 9529

Email : shop@liko.com.sg Website : http://www.liko.com.sg

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim and liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.