

Canon CABLE ID PRINTER MK5000

Delighting You Always

Specifications

Model		MK5000
Printng Method		Thermal Transfer
Printing Resolution (max.)		300 dpi
Printing Speed (Tube)	High Speed	40 mm/s
	Meddle Speed	25 mm/s
	Low Speed	18.5 mm/s
Output Rate ¹ (approx.)	High Speed	55 pcs/min (Ø1.5 - 6.5 mm) 45 pcs/min (Ø7.0 - 10.0 mm)
	Meddle Speed	35 pcs / min
	Low Speed	30 pcs / min
Ink Ribbon	Type	Ribbon Cassette
	For Tube and Label	Black: 150 m / Black: 40 m / White: 85 m
	For Plate	Black: 40 m
Cut Length	Tube	8 - 150 mm
	Label Tape / Plate	4 - 150 mm
Character Size		1.3 mm (only full-width available) 2 mm, 2.6 mm, 3 mm, 4 mm, 6 mm (half-width, full-width available)
Number of Lines		Up to 3 lines
Input Mode		Alphanumeric, Symbol Input
Display	Type	LCD (160 x 64 dots) with backlight
	Capacity	10 characters/line x 2 lines (full-width)
Built-in Memory	Print Data Storage	5,000 characters
	File Storage	250,000 characters, up to 10 folders
Media Cutting Method		Automatic Full-Cut, Automatic Half-Cut
Power Supply	AC Adaptor	100 - 240 V, 50/60 Hz, 0.74A
	Rechargeaber Batteries ¹²	Panasonic eneloop AA size (model: BK-3MCCE) x 6 pieces
Power Consumption	Maximum	25 W
Interface		USB 2.0 Full-Speed (USB 1.1 compatible)
Operating Environment	Temperature	15 - 32.5°C (5 - 18°C with optional tube warmer installed)
	Humidity	10 - 85% RH (with no condensation)
Storage Environment	Temperature	5 - 35°C
	Humidity	10 - 90% RH (with no condensation)
Dimensions (cm) (W x D x H) (approx.)		27.2 x 31.8 x 9.7 cm
Weight (Kg) (approx.)		2.7 Kg (excluding accessories)
Print Media	PVC / Clear Tape	Inner Diameter: Ø1.5 - 10 mm, Ø1.5 - 6.5 mm (when using tube warmer) Thickness: 0.4 - 0.6 mm
	Heat Shrink Tube	Inner Diameter: Ø1.5 - 10 mm Thickness: 0.2 - 0.4 mm
	Label Tape	Tape cassette (White, Yellow, Silver) Width: 6 mm, 9 mm, 12 mm Length: 30 m (White, Yellow), 27 m (Silver)
	Flat Tube ¹³	Diameter: Ø1.5 - 6.5mm Width: 11.2 mm or Less Thickness: 0.4 - 0.6 mm
	Plate ¹³	Width: 8 - 10mm Thickness: 0.5mm

Specifications are subject to change without notice.

¹ Printing on 20 mm long tubes each, five 3 mm full-width characters, continuous print mode, half-cut with normal cutting strength.

¹² Batteries are not included with the printer. Only Panasonic eneloop 1.2V AA rechargeable batteries (model: BK-3MCCE) should be used to avoid printer safety and warranty issues. "Panasonic" and "eneloop" are registered trademarks of Panasonic Group.

¹³ Plate & Flat Tube attachment (optional) is required for printing on plates or flat tubes.

Canon Authorized Distributor

Delighting You Always

Liko TRADE CENTRE PTE LTD

Blk 31, Defu Lane 10, #04-60, Singapore 539212

Tel : (65) 6284 1819 Fax : (65) 6284 9529

Email : shop@liko.com.sg Website : http://www.liko.com.sg

This document is for general information only and contents are subject to change without notice. Errors and omissions excepted. Weights and dimensions are approximates. Options, name and availability may vary by regions. Nothing in this document should be construed as a warranty. We expressly disclaim and liability or contractual obligations in connection with this document. Trademarks belong to their respective owners.