

- Galvanized steel square locked.
- Super flexible and durable for repeated bending and re-positioning.
- Provides protection against most liquids and moisture vapour.
- Small bend radius allows installations in tight quarters with multiple bends.
- PVC jacket won't wrinkle or shrink from cut ends.
- Smooth interior for easy wire pull through.
- Accepts standard liquid-tight fittings.
- Delivers lasting wiring protection in applications that require flexibility, etc.
- Temperature range: - 10°C to + 80°C.
- Use with suitable water tight connector will provide IP66 rating.

PART NUMBER	SIZE	Dim (mm)		Length of Each Roll Mtr	Min Bending Radius mm
		I.D	O.D		
PFC-038B	3/8"	12.8	17.7	50	1-1/2"
PFC-050B	1/2"	16.3	20.3	50	2"
PFC-075B	3/4"	21.3	25.3	50	2-3/4"
PFC-100B	1"	27.1	32.0	30	5"
PFC-125B	1-1/4"	35.8	40.8	25	6"
PFC-150B	1-1/2"	40.7	47.3	25	7"
PFC-200B	2"	52.0	60.0	15	9"
PFC-300BT	3"	75.0	84.0	10	19"

The above data might be changed without prior notice. Special size are available on request.

**** SQUARELOCK TYPE**

